



## Gants dynamiques EN 659

Modèle : EPI-80.0302.049

### Caractéristiques :

- Gant à 5 doigts
- Paume + dos fabriqué en cuir de vachette
- Résistant à la chaleur
- Manche réglable
- Renforcement des artères
- Bande réfléchissante jaune (25mm)
- Doublure + isolant
- Fabriqué en tissu Para aramide
- Membrane respirante
- Coutures réalisées en Kelvar

### Tailles :

De 8 à 11

### Normes :

- EN 659:2003 III Cat.
- A1 :2008 III Cat.

### Niveaux protections :

- Anti abrasion niveau 3
- Anti coupure niveau 2
- Anti déchirure niveau 3
- Anti perforation niveau 3
- Comportement au feu niveau 4
- Dexterité niveau 5



EN 659:2003  
+ A1:2008

**KEVLAR®**





## Dynamics gloves EN659

**Model : EPI-80.0302.049**

**Specifications :**

- 5-finger glove
- Palm + back made of cowhide leather
- Heat resistant
- Adjustable handle
- Strengthening of the arteries
- Yellow reflective strip (25mm)
- Lining + insulation
- Made of Para aramid fabric
- Breathable membrane
- Seams made in Kelvar

**Sizes :**

8 - 11

**Certifications :**

- EN 659:2003 III Cat.
- A1 :2008 III Cat.

**Protect levels :**

- Anti abrasion level 3
- Anti cut level 2
- Anti tear level 3
- Anti-perforation level 3
- Fire behavior level 4
- Dexterity level 5



EN 659:2003  
+ A1:2008

**KEVLAR®**

