

ELKE 8218

Gant de lutte contre l'incendie en cuir, conçu pour offrir une sensibilité de préhension maximale et un confort de port exceptionnel. La combinaison d'une coupe 3D anatomique, d'un cuir de vachette pleine fleur durable à la paume et d'un cuir élan premium souple au dos assure une haute résistance mécanique et thermique, une longue durée de vie et un ajustement naturel qui s'adapte parfaitement à la main.



Couleur:		Beige
Elke Flexi	8218-01	
Elke Evo	8218-02	
Elke Easy	8218-03	
Elke Long	8218-04	
Elke Short	8218-05	

MATÉRIAU EXTÉRIEUR :

- **Dos :** Cuir élan thermostable, à faible retrait et haute résistance à l'abrasion et à la chaleur.
- **Paume :** Cuir de vachette pleine fleur thermostable, à faible retrait et haute résistance à l'abrasion.

COUCHES INTERMÉDIAIRES :

1. Couche isolante : non-tissé en aramide recyclé.
2. Membrane : membrane Porelle®.

DOUBLURE :

- Doublure en aramide.

CARACTÉRISTIQUES TECHNOLOGIQUES ET FONCTIONNELLES

SUPPLÉMENTAIRES :

- Construction anatomique 3D du gant.
- Élément réfléchissant.
- Grand confort et sensibilité exceptionnelle.
- Mousqueton pour fixer les gants à la tenue de feu.
- Grande durabilité.

NORMES :

EN 659:2003+A1:2008



MANCHETTES:



Elke Flexi



Elke Evo



Elke Easy



Elke Long



Elke Short

EUROMAST SARL

Distributeur officiel

Tél : 33 4 79 34 92 15 E-mail : info@materiel-pompier.com

Adresse : Savoie Hexapôle, 101 Rue Louis Armand, 73420 Mery, France

Web: www.materiel-pompier.com

Arclin®, le logo Arclin, Kevlar®, Nomex®, Firepoint® et toutes les marques commerciales et de service portant les mentions ™, SM ou ® appartiennent à Arclin et à ses filiales, sauf indication contraire. © 2026 Arclin. Tous droits réservés



Co-funded by
the European Union

CE 1023

05/2026

ELKE 8218

Mesure :	Avant lavage :
Résistance à l'abrasion	3
Résistance à la coupe (paume)	5
Résistance à la déchirure	4
Résistance à la perforation	3
Comportement au feu	4
Résistance à la chaleur convective	4
Résistance à la chaleur radiante	3
Résistance à la chaleur de contact	2
Dextérité	4

GAMME DE TAILLES :

cm	12,7 - 15,2	15,2 - 16,5	16,5 - 19	19 - 21,6	21,6 - 24,2	24,2 - 26,7	26,7 - 29,2	29,2 - 30,4	30,4 - 32,9
taille	5 (XXS)	6 (XS)	7 (S)	8 (M)	9 (L)	10 (XL)	11 (2XL)	12 (3XL)	13 (4XL)

ENTRETIEN ET MAINTENANCE :

Choisissez un programme de lavage court, plus écologique, à 40 °C.



PROCÉDURE : retirez les salissures grossières après chaque utilisation. Avant le lavage, fermez les bandes velcro et retirez les boutons-pression. Utilisez une lessive liquide. Lavez sur un programme court.

POUR UN MEILLEUR AJUSTEMENT DU GANT : remodelez le gant plusieurs fois après le lavage et pendant le séchage. Ne le séchez pas à la lumière directe du soleil ni près d'une source de chaleur, n'utilisez pas de sèche-linge. Rangez les gants dans un endroit sec.

Pour en savoir plus sur l'entretien et la maintenance, consultez : www.holik.com > Technologies > Care&Maintenance



ELKE 8218

A leather firefighting glove designed to provide maximum grip sensitivity and exceptional wearing comfort. The combination of an anatomical 3D cut, durable full-grain cowhide leather in the palm, and soft premium elk grain leather on the back ensures high mechanical and thermal resistance, long service life, and a natural fit that adapts perfectly to the hand.



Barva:		Beige
Elke Flexi	8218-01	
Elke Evo	8218-02	
Elke Easy	8218-03	
Elke Long	8218-04	
Elke Short	8218-05	

UPPER MATERIAL:

- **Back:** Thermostable elk grain leather with minimal shrinkage and high resistance to abrasion and heat.
- **Palm:** Thermostable full-grain cowhide leather with minimal shrinkage and high abrasion resistance.

INTERMEDIATE LAYERS:

3. Insulation layer - recycled aramid non-woven fabric.
4. Membrane - Porelle® membrane.

LINING:

- Aramid lining.

ADDITIONAL TECHNOLOGICAL AND FUNCTIONAL FEATURES:

- Anatomical 3D glove construction.
- Reflective element.
- High comfort and exceptional sensitivity.
- Carabiner for attaching the gloves to firefighting gear.
- High durability.

STANDARDS:

EN 659:2003+A1:2008



CUFFS:



Elke Flexi



Elke Evo



Elke Easy



Elke Long



Elke Short

EUROMAST SARL

Distributeur officiel

Tél : 33 4 79 34 92 15 E-mail : info@materiel-pompier.com

Adresse : Savoie Hexapôle, 101 Rue Louis Armand, 73420 Mery, France

Web: www.materiel-pompier.com

Arclin®, the Arclin logo, Kevlar®, Nomex®, Firepoint® and all trademarks and service marks denoted with ™, SM or ® are owned by Arclin and its affiliates unless otherwise noted. © 2026 Arclin. All rights reserved



Co-funded by
the European Union

CE 1023

05/2026

ELKE 8218

Measurement:	Before washing:
Abrasion resistance	3
Blade cut resistance (palm part)	5
Tear resistance	4
Puncture resistance	3
Burning behaviour	4
Convection heat resistance	4
Radiant heat resistance	3
Contact heat resistance	2
Dexterity	4

SIZE ASSORTMENT:

cm 	12,7-15,2	15,2-16,5	16,5 - 19	19 - 21,6	21,6 - 24,2	24,2 - 26,7	26,7 - 29,2	29,2 - 30,4	30,4-32,9
size	5 (XXS)	6 (XS)	7 (S)	8 (M)	9 (L)	10 (XL)	11 (2XL)	12 (3XL)	13 (4XL)

CARE & MAINTENANCE:

Choose a more ecological short washing program at 40 °C.



PROCEDURE: Remove coarse dirt after each use. Before washing, fasten the Velcro fasteners and remove the snaps. Use a liquid detergent. Wash on a short programme.

TO MAKE THE GLOVE FIT BETTER: Shape the glove several times after washing and during drying. Do not dry in direct sunlight or heat sources, do not use a tumble dryer. Store the gloves in a dry environment.

For more about Washing & Maintenance, visit:
www.holik.com > Technologies > Care&Maintenance

